

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

1. (canceled)
2. (previously presented) An intracorporal device comprising:
 - a) a helically wound coil having a plurality of windings forming a coil length;
 - b) a thermoplastic polymer tube disposed about a portion of the coil length;
 - c) a plurality of discrete affixation points disposed along the coil length wherein each discrete affixation point fixes the thermoplastic tube to two or more coil windings, wherein each discrete affixation point is separate from other discrete affixation points by areas where the thermoplastic polymer tube is not affixed to the coil, wherein the plurality of discrete affixation points includes 10 discrete affixation points disposed along the coil length.
3. (canceled)
4. (previously presented) An intracorporal device comprising:
 - a) a helically wound coil having a plurality of windings forming a coil length;
 - b) a thermoplastic polymer tube disposed about a portion of the coil length;
 - c) a plurality of discrete affixation points disposed along the coil length wherein each discrete affixation point fixes the thermoplastic tube to two or more coil windings, wherein each discrete affixation point is separate from other discrete affixation points by areas where the thermoplastic polymer tube is not affixed to the coil, wherein the plurality of discrete affixation points form a non-uniform pattern along the coil length, wherein the plurality of discrete affixation points has a density of discrete affixation points per unit length of coil that decreases along the coil length.
- 5-9. (canceled)

10. (currently amended) An intracorporal device comprising:
- a) a helically wound coil having a plurality of windings having an outer perimeter and forming a coil length;
 - b) a thermoplastic polymer tube circumferentially disposed about a portion of the coil length;
 - c) a plurality of discrete affixation points, each of the affixation points disposed about only a portion of the outer perimeter of the helically wound coil and along a portion of the coil length, wherein each discrete affixation point fixes the thermoplastic tube to two or more coil windings, wherein each discrete affixation point is separated from other discrete affixation points by areas where the polymer tube is not affixed to the coil; and

~~The intracorporal device according to claim 9,~~ wherein the plurality of discrete affixation points includes 10 discrete affixation points disposed along the coil length.

11. (canceled)

12. (currently amended) An intracorporal device comprising:
- a) a helically wound coil having a plurality of windings having an outer perimeter and forming a coil length;
 - b) a thermoplastic polymer tube circumferentially disposed about a portion of the coil length;
 - c) a plurality of discrete affixation points, each of the affixation points disposed about only a portion of the outer perimeter of the helically wound coil and along a portion of the coil length, wherein each discrete affixation point fixes the thermoplastic tube to two or more coil windings, wherein each discrete affixation point is separated from other discrete affixation points by areas where the polymer tube is not affixed to the coil;

wherein the plurality of discrete affixation points form a non-uniform pattern along the coil length; and

~~The intracorporal device according to claim 11,~~ wherein the plurality of discrete affixation points has a density of discrete affixation points per unit length of coil that decreases along the coil length.

13-16. (canceled)

17. (previously presented) A medical device comprising:

- a) an elongate shaft;
- b) a helically wound coil having a plurality of windings forming a coil length disposed about a portion of the elongate shaft;
- c) a thermoplastic polymer tube circumferentially disposed about a portion of the coil length; and
- d) five or more discrete affixation points disposed along the coil length, wherein each discrete affixation point fixes the thermoplastic polymer tube to two or more coil windings, wherein each discrete affixation point is separated from other discrete affixation points by areas where the polymer tube is not affixed to the coil.

18. (previously presented) A medical device comprising:

- a) an elongate shaft;
- b) a helically wound coil having a plurality of windings forming a coil length disposed about a portion of the elongate shaft;
- c) a thermoplastic polymer tube circumferentially disposed about a portion of the coil length; and
- d) a plurality of discrete affixation points disposed along the coil length, wherein each discrete affixation point fixes the thermoplastic polymer tube to two or more coil windings, wherein each discrete affixation point is separated from other discrete affixation points by areas where the polymer tube is not affixed to the coil, wherein the plurality of discrete affixation points includes 10 discrete affixation points disposed along the coil length.

19. (original) The medical device according to claim 17, wherein the plurality of discrete affixation points form a non-uniform pattern along the coil length.

20. (previously presented) A medical device comprising:

- a) an elongate shaft;

b) a helically wound coil having a plurality of windings forming a coil length disposed about a portion of the elongate shaft;

c) a thermoplastic polymer tube circumferentially disposed about a portion of the coil length; and

d) a plurality of discrete affixation points disposed along the coil length, wherein each discrete affixation point fixes the thermoplastic polymer tube to two or more coil windings, wherein each discrete affixation point is separated from other discrete affixation points by areas where the polymer tube is not affixed to the coil, wherein the plurality of discrete affixation points form a non-uniform pattern along the coil length, wherein the plurality of discrete affixation points has a density of discrete affixation points per unit length of coil that decreases along the coil length.

21. (original) The medical device according to claim 17, wherein the plurality of discrete affixation points form a uniform pattern along the coil length.

22. (previously presented) The medical device according to claim 17, wherein each discrete affixation point fixes 3 to 10 coil windings to the thermoplastic tube.

23. (original) The medical device according to claim 17, wherein each discrete affixation point is a discrete element aligned orthogonal to the windings.

24. (original) The medical device according to claim 17, wherein each discrete affixation point is a element having a width of 0.1 to 0.5 mm and a length of 0.1 to 0.3 mm.

25. (previously presented) The medical device of claims 17, wherein the medical device comprises a guidewire;

the elongate shaft has a proximal end and an opposing distal end; and

the helically wound coil is disposed about a portion of the distal end.

26. (previously presented) A guidewire comprising:

a) an elongate shaft having a proximal end and an opposing distal end;

- b) a helically wound coil having a plurality of windings forming a coil length disposed about a portion of the distal end;
 - c) a thermoplastic tube circumferentially disposed about a portion of the coil length;
- and
- d) a plurality of discrete affixation points disposed along the coil length, wherein each discrete affixation point fixes the thermoplastic polymer tube to two or more coil windings, wherein each discrete affixation point is separated from the other discrete affixation points by areas where the polymer tube is not affixed to the coil, wherein the plurality of discrete affixation points form a non-uniform pattern along the coil length.

27. (canceled)

28. (previously presented) A guidewire comprising:

- a) an elongate shaft having a proximal end and an opposing distal end;
 - b) a helically wound coil having a plurality of windings forming a coil length disposed about a portion of the distal end;
 - c) a thermoplastic tube circumferentially disposed about a portion of the coil length;
- and
- d) a plurality of discrete affixation points disposed along the coil length, wherein each discrete affixation point fixes the thermoplastic polymer tube to two or more coil windings, wherein each discrete affixation point is separated from the other discrete affixation points by areas where the polymer tube is not affixed to the coil, wherein the plurality of discrete affixation points form a non-uniform pattern along the coil length, wherein the plurality of discrete affixation points has a density of discrete affixation points per unit length that decrease along the coil length.

29-32. (canceled)

33. (original) The guidewire according to claim 28, wherein the plurality of discrete affixation points has a density of discrete affixation points per unit length that decrease along the coil length, wherein the thermoplastic polymer tube has a proximal end and a distal end and

where the density of discrete affixation points per unit length decreases from the proximal end to the distal end.

34. (withdrawn) A process for forming and intracorporal device comprising;
a) disposing a thermoplastic polymer sleeve circumferentially disposed about a portion of a helically wound coil having a plurality of windings forming a coil length; and
b) forming a plurality of discrete affixation points along the coil length, wherein each discrete affixation point fixes the thermoplastic polymer sleeve to two or more coil windings.

35. (withdrawn) The process according to claim 34, wherein the forming a plurality of discrete affixation points comprises thermal energy.

36. (withdrawn) The process according to claim 34, wherein the forming a plurality of discrete affixation points comprises laser welding.

37. (withdrawn) The process according to claim 34, wherein the forming a plurality of discrete affixation points comprises laser diode welding.

38. (withdrawn) The process according to claim 34, wherein the forming a plurality of discrete affixation points includes forming 10 elements disposed along the coil length.

39. (withdrawn) The process according to claim 34, wherein the forming a plurality of discrete affixation points includes forming a non-uniform pattern of discrete affixation points along the coil length.

40. (withdrawn) The process according to claim 39, wherein the forming a plurality of discrete affixation points includes forming a plurality of discrete affixation points having a density of discrete affixation points per unit coil length that decreases along the coil length.

41. (withdrawn) The process according to claim 34, wherein the forming a plurality of discrete affixation points includes forming a uniform pattern of discrete affixation points along the coil length.

42. (withdrawn) The process according to claim 34, wherein the forming a plurality of joining elements includes coupling 3 to 10 coil windings.

43. (withdrawn) The process according to claim 34, wherein the forming a plurality of discrete affixation points includes forming discrete affixation points aligned orthogonal to the windings.

44. (withdrawn) The process according to claim 34, wherein the forming a plurality of discrete affixation points includes forming discrete affixation elements having a width of 0.1 to 0.5 mm and a length of 0.1 to 0.3 mm.

45. (withdrawn) The process according to claim 34, wherein the forming a plurality of discrete affixation points includes forming discrete affixation elements by preferentially heating the thermoplastic sleeve at discrete points sufficient to flow thermoplastic polymer around two or more windings at each discrete affixation point.

46. (withdrawn) A product produced by the process of claim 34.